



## AMMERAAL AMRA 25 DE

### APPLICATIONS

- Highly sanitary, non-porous.
- Use in high contamination environments.
- Cheese, milk, meat and poultry industries.
- 100% non-fraying
- Easy to join using low cost equipment.
- Low stretch, low noise and easy to clean with water up to 100°C

### CONSTRUCTION

Homogeneous, 55 Shore D, synthetic material.

**Top surface:** smooth

**Bottom surface:** low friction, diamond profile

### CHARACTERISTICS

- Ammeraal Amra 25 DE available in either blue or natural.
- Homogeneous food grade material.
- Meets F.D.A requirements for contact with dry & bulk foods (regulation No.21CFR 177-1590) and fatty & wet foods (Regulation No.CFR 177-2600)
- No foreign matter is included in formulation.
- Odour and taste free, has excellent resistance to oil, fats and is UV stable

### TECHNICAL DATA

<b>Thickness:</b>	2.5mm		
<b>Weight:</b>	3.0kg/m <sup>2</sup>		
<b>Max width:</b>	1000mm		
<b>Min Pulley:</b>	88mm (180° wrap) 80mm (120° wrap)		
<b>Joining:</b>	Mirror Welders or fasteners		
<b>Belt Support:</b>	Rollers and decking		
<b>Work Load:</b>	2.8N/mm will result in 1% elongation		
<b>Temp:</b>	<b>Operating:</b> -20°C to +80°C	<b>Cleaning:</b>	+100°C