



AMMERAAL AMRA 30

APPLICATIONS

- Highly sanitary, non-porous.
- Use in high contamination environments.
- Cheese, milk, meat and poultry industries.
- 100% non-fraying
- Easy to join using low cost equipment.
- Low stretch, low noise and easy to clean with water up to 100°C

CONSTRUCTION

Homogeneous, 55 Shore D, synthetic material.

Top surface: smooth

Bottom surface: smooth

CHARACTERISTICS

- Ammeraal Amra 30 available in either blue or natural.
- Homogeneous food grade material.
- Meets F.D.A requirements for contact with dry & bulk foods (regulation No.21CFR 177-1590) and fatty & wet foods (Regulation No.CFR 177-2600)
- No foreign matter is included in formulation.
- Odour and taste free, has excellent resistance to oil, fats and is UV stable

TECHNICAL DATA

| | |
|----------------------|--|
| Thickness: | 3.0mm |
| Weight: | 3.5kg/m ² |
| Max width: | 1000mm |
| Min Pulley: | 105mm (180° wrap) 80mm (120° wrap) |
| Joining: | Mirror Welders or fasteners |
| Belt Support: | Rollers and decking |
| Work Load: | 3.6N/mm will result in 1% elongation |
| Temp: | Operating: -20°C to +70°C Cleaning: +100°C |