



## AMMERAAL BB 20

### APPLICATIONS

- Use in high contamination environments.
- Processing applications like cheese, milk, meat and poultry industries
- Dough carrying and dough cutting application.
- High wear application such as Brick and Tile Industry, Timber, Steel processing accumulation

### CONSTRUCTION

Homogeneous 95 Shore A PU. Meets FDA requirements

**Top surface:** smooth      **Bottom surface:** smooth

### CHARACTERISTICS

- Ammeraal Big Bear 20 available in either Blue or Natural.
- Highly sanitary, cut resistant, abrasive resistant, oil resistant, non-porous
- Low noise, easy to clean
- 100% non-fraying.
- Oil and grease resistant, easy to clean surfaces.
- Meets F.D.A requirements for contact with dry & bulk foods (Regulation No. CFR 177-1680) and fatty and wet foods (Regulation No. CFR 177-2600).
- No foreign matter is included in formulation.

### TECHNICAL DATA

<b>Thickness:</b>	2.0mm
<b>Weight:</b>	2.4kg/m <sup>2</sup>
<b>Max width:</b>	1000mm
<b>Min Pulley:</b>	30mm (180° wrap)
<b>Joining:</b>	Mirror Welded, Fasteners
<b>Belt Support:</b>	Rollers
<b>Work Load:</b>	1.2N/mm will result in 1% elongation
<b>Temp:</b>	-20°C to +70°C