



AMMERAAL BB 20 DE

APPLICATIONS

- Highly sanitary, cut resistant, abrasive resistant, non-porous
- Use in high contamination environments.
- Processing applications like cheese, milk, meat and poultry industries
- 100% non-fraying.
- Dough carrying and dough cutting application.
- Easy to join using low cost equipment.
- Low noise, easy to clean
- High wear application such as Brick & Tile Industries. Timber, Steel processing accumulation

CONSTRUCTION

Homogeneous, 95 Shore A oil and grease resistant. P.U. Easy to clean surfaces.

Top surface: smooth

Bottom surface: low friction, diamond profile

CHARACTERISTICS

- Ammeraal Big Bear 20 DE available in either Blue or Ivory.
- Homogeneous food grade material.
- Meets F.D.A requirements for contact with dry & bulk foods (regulation No. CFR 177-1590) and fatty and wet foods (Regulation No. CFR 177-2600).
- No foreign matter is included in formulation.

TECHNICAL DATA

Thickness:	2.0mm
Weight:	2.3kg/m ²
Max width:	1000mm
Min Pulley:	30mm (180° wrap)
Joining:	Mirror Welded, finger, overlap fasteners
Belt Support:	Rollers
Work Load:	1.2N/mm will result in 1% elongation
Temp:	-20°C to +70°C