



## AMMERAAL BB 25

### APPLICATIONS

- Highly sanitary, cut resistant, abrasive resistant, non-porous
- Use in high contamination environments.
- Processing applications like cheese, milk, meat and poultry industries
- 100% non-fraying.
- Dough carrying and dough cutting application.
- Easy to join using low cost equipment.
- Low noise, easy to clean
- High wear application such as Brick & Tile Industries. Timber, Steel processing accumulation

### CONSTRUCTION

Homogeneous, 95 Shore A oil and grease resistant. P.U. Easy to clean surfaces.

**Top surface:** smooth

**Bottom surface:** smooth

### CHARACTERISTICS

- Ammeraal Big Bear 25 available in either Blue or Ivory.
- Homogeneous food grade material.
- Meets F.D.A requirements for contact with dry & bulk foods (regulation No. CFR 177-1590) and fatty and wet foods (Regulation No. CFR 177-2600).
- No foreign matter is included in formulation.

### TECHNICAL DATA

<b>Thickness:</b>	2.5mm
<b>Weight:</b>	3.0kg/m <sup>2</sup>
<b>Max width:</b>	1000mm
<b>Min Pulley:</b>	38mm (180° wrap)
<b>Joining:</b>	Mirror Welded, finger, overlap fasteners
<b>Belt Support:</b>	Rollers
<b>Work Load:</b>	1.6N/mm will result in 1% elongation
<b>Temp:</b>	-20°C to +70°C